

QA Center Performance Edition

Installation and Configuration Guide

Release 05.01



Technical support is available from our Technical Support Hotline or via our FrontLine Support Web site.

Technical Support Hotline:
1-800-538-7822

FrontLine Support Web Site:
<http://frontline.compuware.com>

This document and the product referenced in it are subject to the following legends:

Access is limited to authorized users. Use of this product is subject to the terms and conditions of the user's License Agreement with Compuware Corporation.

© 1998-2004 Compuware Corporation. All rights reserved. Unpublished - rights reserved under the Copyright Laws of the United States.

U.S. GOVERNMENT RIGHTS

Use, duplication, or disclosure by the U.S. Government is subject to restrictions as set forth in Compuware Corporation license agreement and as provided in DFARS 227.7202-1(a) and 227.7202-3(a) (1995), DFARS 252.227-7013(c)(1)(ii)(OCT 1988), FAR 12.212(a) (1995), FAR 52.227-19, or FAR 52.227-14 (ALT III), as applicable. Compuware Corporation.

This product contains confidential information and trade secrets of Compuware Corporation. Use, disclosure, or reproduction is prohibited without the prior express written permission of Compuware Corporation.

Compuware, ActiveAnalysis, ActiveData, Interval, QACenter, QADirector, QALoad, QARun, Reconcile, TestPartner, TrackRecord, and WebCheck are trademarks or registered trademarks of Compuware Corporation.

Acrobat® Reader copyright © 1987-2002 Adobe Systems Incorporated. All rights reserved. Adobe, Acrobat, and Acrobat Reader are trademarks of Adobe Systems Incorporated.

All other company or product names are trademarks of their respective owners.

US Patent Nos.: Not Applicable.

Doc. CWQLIX510
April 6, 2004




Table of Content

Introduction

Who Should Read This Guide	5
Related Publications	5
World Wide Web Information	6
Getting Help	7

Chapter 1

Getting Started

Overview of QACenter Performance Edition	9
Installation Types	10
Before Installation	10

Chapter 2

Installing QALoad

Planning Your Installation	13
QALoad Concurrent Conductor Licensing	16
System Requirements	17
General Windows Installation Requirements	17
Additional Requirements by Component	17
Middleware-Specific Requirements	18
Installing QALoad	25
UNIX Player Installation	29
Installing Via Tar File	29
Installing Via Package	31


Chapter 3

Maintaining the Installation

Accessing Maintenance Mode	39
Modifying an Installation	40
Repairing an Installation	40
Removing a Product	41

Index

Introduction



The QACenter Performance Edition Installation and Configuration Guide provides information and procedures to install and maintain QALoad.

When installing File-AID/CS, refer to the *File-AID/CS Installation Guide* for installation instructions.

Who Should Read This Guide

This guide is intended for administrators who are installing and configuring QACenter products; it does not contain reference or usage information. You can find that information in your product's online help facility and documentation set.

Compuware assumes that you are familiar with basic Microsoft Windows navigation. If this is not the case, familiarize yourself with the documentation for Microsoft Windows before reading this guide.

Related Publications

The QACenter Performance Edition installation documentation set is comprised of the following:

- ◆ The QACenter Performance Edition Installation and Configuration Guide, which includes system requirements and instructions for installing QALoad.
- ◆ The *Distributed License Management Installation Guide*, which includes instructions for licensing your QACenter product.
- ◆ The *File-AID/CS Installation Guide*, which includes system requirements and instructions for installing File-AID/CS.

All of these books are provided in PDF format only. You can access the online versions of the QACenter Performance Edition Installation and Configuration Guide and the *Distributed License Management Installation Guide* from the CD browser (see the instructions that follow) or from Compuware's FrontLine customer support Web site at <http://front-line.compuware.com>.

Viewing and Printing Online Books

To access these online books:

- 1 Insert the QACenter CD into the CD-ROM drive. If the CD browser does not automatically start, navigate to the CD's root directory and run `setup.exe`.
- 2 Click **View QACenter Documentation**. The documentation bookshelf opens in Acrobat Reader. (If necessary, Acrobat Reader can be installed from the QACenter CD by clicking **Install 3rd Party Software**, then clicking **Install Adobe Acrobat Reader**.)
- 3 From the bookshelf, select the installation guide that you wish to view.

Because PDF is based on PostScript, a PostScript printer is the most reliable way to print online books. In most cases, you can also print PDF files to PCL printers. If you cannot print the PDF files to your printer, refer to Adobe's Web site at <http://www.adobe.com> for troubleshooting information.

World Wide Web Information

To access Compuware Corporation's site on the World Wide Web, point your browser at <http://www.compuware.com>. The Compuware site provides a variety of product and support information.

FrontLine Support Web Site: You can access online technical support for Compuware products via the FrontLine support web site. FrontLine provides fast access to critical information about your QACenter product. You can read or download documentation, frequently asked questions, and product fixes, or e-mail your questions or comments. To access FrontLine, follow these steps:

- 1 Open a web browser and go to: <http://frontline.compuware.com>
The Welcome to FrontLine page appears.
- 2 On the right side of the page, enter your login ID and password and click the **Login** button.

- Note:** If you are a first-time visitor, click the **Register** button to receive your free password to access FrontLine. After you complete the registration form, your login ID and password will be e-mailed to you and your account will be activated.
- 3 From the drop-down list in the center of the page, select a product and click the **Go** button. You will see the product's FrontLine home page, where you can access documentation, technical information, fixes, and other support items.

Getting Help

At Compuware, we strive to make our products and documentation the best in the industry. Feedback from our customers helps us maintain our quality standards. If you need support services, please obtain the following information before calling Compuware's 24-hour product support hotline:

- ◆ The name, release (version), and build number of the QACenter product. This information is displayed when you select the About command from your product's Help menu. The name and release are also on the covers of the product documentation.
- ◆ Installation information, including installed options, whether the product uses local or network databases, whether it is installed in the default directories, whether it is a standalone or network installation, and whether it is a client or server installation.
- ◆ Environment information, such as the operating system and release on which the product is installed, memory, hardware/network specifications, and the names and releases of other applications that were running.
- ◆ The location of the problem in the QACenter product software, and the actions taken before the problem occurred.
- ◆ The exact product error message, if any.
- ◆ The exact application, licensing, or operating system error messages, if any.

- ◆ Your Compuware client, office, or site number, if available



Customer Support

Compuware Corporation

One Campus Martius


Detroit, MI 48226-5099

1-800-538-7822

<http://frontline.compuware.com>

Chapter 1

Getting Started



- ◆ Overview of QACenter Performance Edition
- ◆ Installation Types
- ◆ Before Installation

Overview of QACenter Performance Edition

QACenter Performance Edition helps organizations conduct realistic, in-depth, and repeatable performance testing on applications throughout the enterprise. With a powerful combination of load testing, resource utilization, and user experience monitoring tools, QACenter Performance Edition helps organizations find and resolve performance problems quickly.

The QACenter Performance Edition suite of automated testing and test management tools includes:

QALoad: Load tests enterprise client/server systems and associated networks. QALoad can stress your system by simulating thousands of users simultaneously performing different operations. It creates and runs test scripts that can simulate application transactions on the system without involving end users or their equipment.

File-AID/CS: A data management tool that saves time and reduces the level of complexity required in preparing and managing data for testing. It provides facilities for easily copying, transforming, creating, comparing, and modifying data; validating test results; and restoring test data to its baseline state. File-AID/CS is an excellent tool for any testing project where ensuring data and application reliability is critical.

In addition to the QACenter Performance Edition suite of products, the QACenter Performance Edition CD includes Adobe Acrobat Reader, Microsoft Internet Explorer, Microsoft Virtual Machine, and Java 2 SDK

version 1.3.0_02 installation programs. To install one or more of these products from the QACenter Performance Edition CD, click **Install 3rd Party Software**, then click on the product installation you would like to perform.

Installation Types

Before you begin, determine the type of installation you need to perform:

Initial Installation: An initial installation is the first-time installation of a product on your computer. See the installation chapter for each product for instructions.

Modify: A modification of the product installation occurs when you add or remove one or more of a product's components, but not all of them. See the maintenance chapter for instructions.

Repair: A repair installation may be necessary due to a corruption of a program or the inadvertent deletion of the product. See the maintenance chapter for instructions.

Remove: A remove or uninstallation removes all the components of a product. See the maintenance chapter for instructions.

Upgrade: Normally, an upgrade to a new release of a product does not require that you uninstall the current release first. If there are special concerns with regard to upgrading a QACenter product, they are explained in the product's installation chapter.

Before Installation

Before installing any QACenter product, you should carefully review the following information:

System Requirements

Review the system requirements to ensure that you meet the prerequisites for the successful installation and operation of the product. System requirements are listed in the Release Notes as well as in each product's installation chapter in this book.

Release Notes

Review the Release Notes for information about new features, technical notes, and known issues that may enhance or impact your product's

performance. Release Notes contain recent changes that may not be included in your QACenter product documentation.

Release Notes can be viewed from the QACenter CD or on FrontLine, Compuware's product support web site. The Release Notes on FrontLine are periodically updated as new information becomes available.

To access the Release Notes from the QACenter CD, follow these steps:


- 1 Insert the QACenter CD into the CD-ROM drive. If the CD browser does not start automatically, navigate to the CD's root directory and run `setup.exe`.
- 2 Click **View QACenter Release Notes**. The Release Notes open in your default Web browser.
- 3 Read the Release Notes online, or print the document.
- 4 After reading and/or printing the Release Notes, close the document to return to the CD browser.

To access the Release Notes on FrontLine, follow these steps:

- 1 Open a web browser and go to: <http://frontline.compuware.com>
The Welcome to FrontLine page appears.
 - 2 On the right side of the page, enter your login ID and password and click the **Login** button.
- Note:** If you are a first-time visitor, click the **Register** button to receive your free password to access FrontLine. After you complete the registration form, your login ID and password will be e-mailed to you and your account will be activated.
- 3 From the drop-down list in the center of the page, select a product and click the **Go** button. You will see the product's FrontLine home page.
 - 4 On the left side of the product's homepage, select the **Documentation** link. You will see the product's documentation page, which includes links to Release Notes and other documentation types.
 - 5 Click the **HTML** or **PDF** icons to view documents.

Chapter 2

Installing QALoad



- ◆ Planning Your Installation
- ◆ System Requirements
- ◆ Installing QALoad
- ◆ UNIX Player Installation

Planning Your Installation

QALoad consists of separate, installable components for script recording and editing, load testing and test execution management, virtual user generation, results analysis, server monitoring, and network traffic generation. (In addition, there are components related to specific middleware types.) Not all components are required in every testing situation. The following table describes what each component does, and why and where it should be installed. Please refer to this table to determine which components are appropriate for your load testing requirements. For supported operating systems and minimum system requirements for each component, see “[System Requirements](#)” on page 17.

After reviewing this table, carefully follow the instructions in “[Installing QALoad](#)” on page 25 to ensure that you install only those components that are appropriate for your testing needs.

Table 2-1. QALoad Component Descriptions

Component	Purpose	Where to Install
QALoad Script Development Workbench	Contains the elements necessary for recording, converting, compiling, and modifying test scripts.	Typically installed on the same workstation (Windows) as the QALoad Conductor and QALoad Analyze components and on the workstation that has the appropriate application browser you're recording transactions from.
QALoad Conductor	<p>Controls the QALoad Players and manages tests. It is the center for application playback.</p> <p>In addition, the QALoad Conductor is where you check out licenses for virtual users for your load tests. For further information, see "QALoad Concurrent Conductor Licensing" on page 16.</p>	<p>Must be installed on the same workstation as QALoad Analyze for reporting purposes.</p> <p>Most users will install QALoad Conductor on the same workstation as the QALoad Script Development Workbench.</p>
QALoad Player	Emulates users by running test scripts that mimic user transactions. QALoad Players are available for a number of operating environments. The QALoad Player is the most performance-sensitive component of QALoad, as it is responsible for creating hundreds or thousands of concurrent virtual users from the same workstation.	<p>If you intend to run large volume load tests, Compuware recommends that you install the QALoad Player on a powerful and dedicated workstation. No other resource-intensive processes should be installed or running at the same time the QALoad Player is in use for load testing.</p> <p>In addition, Compuware recommends that to make load test management easier, you do not run both the Server Analysis Agent and QALoad Player simultaneously on the same workstation.</p>

Table 2-1. QALoad Component Descriptions

Component	Purpose	Where to Install
QALoad Analyze	The key component for the analysis of statistics measured during the load test. Lets you correlate and report on load testing performance and server utilization statistics gathered during the test.	Typically installed on the same Windows workstation as the QALoad Script Development Workbench.
Server Analysis Agent	Monitors the servers and applications that a load test impacts, for example, web server, application server, database server, and database.	<p>Must be installed with the Windows version of the QALoad Player (for automatic discovery and control).</p> <p>Although the Server Analysis Agent installs with the Windows QALoad Player, Compuware recommends that you do not run virtual users from the same workstations that you are trying to monitor in order to ensure test result accuracy.</p>
Vantage Agent	Captures network traffic information from a remote machine. The captured data can be used to profile the effect of the network on an application's performance.	<p>Must be installed on the same machine as the QALoad Conductor.</p> <p>Note: If Application Vantage is installed on the QALoad Conductor machine, or if the machine's operating system is Microsoft Windows XP, you must install the Application Vantage Remote Agent or Application Expert. The Vantage Agent version must match the version of the Vantage Console installed.</p>

Table 2-1. QALoad Component Descriptions

Component	Purpose	Where to Install
NetLoad Server	The NetLoad UDP and TCP servers are required only when using the TCP and UDP options within NetLoad. They are not required for any other middleware options and need only be installed if using NetLoad.	There are no special considerations for where to install the NetLoad servers.

QALoad Concurrent Conductor Licensing

Required: To use this feature, you must install the License Manager for Windows or UNIX on a license server. Refer to the *Distributed License Management Installation Guide* guide for instructions on installing the License Manager. For information on checking out virtual user licenses in general, refer to the *QALoad Conductor Online Help Checking out virtual user licenses* topic.

QALoad's concurrent Conductor licensing, also referred to as Bulk Check-out, allows a number of Conductors to share a pool of virtual users. The number of concurrent Conductors is dependent on the license purchased. To determine how many Conductors and virtual users you are licensed for, view your license using the *Compuware License Administration Utility* (LAU). From the **Start** menu, choose **Programs>Compuware>License Manager>License Administration Utility**. The number of licensed Conductors will be the value associated with the `QALoad_Conductor` string located in the **Licenses** area in the **Product/Version** column. The number of licensed virtual users will be the value associated with the `QALoad` string.

If your license allows a single Conductor only, then the Bulk Checkout feature of QALoad does not apply to you. For information on how to use the LAU, see the *License Administration Utility Help*. From the **Start** menu, choose **Programs>Compuware>License Manager>License Administration Utility Help**.

Tip: You can also view the number of licensed virtual users by choosing **Tools>Licensing** from the *QALoad Conductor* menu. On the *License Information* dialog box, in the **Current License Information** area, you will see the **Total number of Virtual User licenses**.

System Requirements

This section describes the general requirements for running a complete installation of QALoad, as well as requirements for each individual QALoad component that may be installed separately, and requirements for the individual middlewares. Review each section to determine which requirements apply to your configuration.

General Windows Installation Requirements

QALoad has the following minimum system requirements:

- ◆ Mid-level Pentium III PC with 256 MB of RAM. RAM requirements may vary by middleware.
- ◆ 285 MB available disk space.
- ◆ Microsoft Windows NT 4.0 Workstation/Server with Service Pack 5 or Service Pack 6a, Windows 2000 Service Pack 2, or Windows XP Professional.

Required: QALoad can be installed on the Japanese, Chinese, and Korean versions of Windows NT 4.0 Workstation/Server with Service Pack 5 or Service Pack 6a, Windows 2000 Service Pack 2, or Windows XP Professional.

- ◆ Microsoft Internet Explorer 5.5 or later. (Netscape Communicator 4.7.x, or Netscape 6.x can also be used for Analyze and WWW recording in the Script Development Workbench. Netscape 7 is not supported.)
- ◆ Adobe Acrobat or Acrobat Reader (provided on the QACenter CD) to view the online books in PDF format.

Administrative Rights

Installing QALoad requires full administrative rights.

Additional Requirements by Component

The following sections detail the system requirements that differ by QALoad component. Requirements also vary by middleware; see “[Middleware-Specific Requirements](#)” on page 18.

QALoad Script Development Workbench

- ◆ Microsoft Visual C++ Version 6.0 Service Pack 3, Visual Studio .NET, or Visual Studio .NET 2003 for script compilation and script validation.

Note: Only Visual C++ Version 6 is supported for the Citrix and SAP 6.20 middlewares.

QALoad Conductor Requirements

- ◆ TCP/IP communications.

QALoad Analyze Requirements

- ◆ MAPI32-compliant mail program such as Microsoft Outlook (required for use of timing file mailing utility).

Server Analysis Agent Requirements

- ◆ TCP/IP communications.

Note: The Server Analysis Agent must be installed on the same Workstation/Server as the QALoad Player and therefore shares the same system requirements.

QALoad Windows Player Requirements

- ◆ Java 2 Runtime Environment 1.3 or 1.4 (1.3.0_02 is provided on the QACenter CD) for running Java scripts.
- ◆ TCP/IP communications.

Middleware-Specific Requirements

In addition, your Windows system may need to meet specific requirements to support the middleware you will be testing. For middleware-specific requirements, see the following sections:

- ◆ [“Oracle 7.3.x Requirements”](#) on page 19
- ◆ [“Oracle Net8 Requirements”](#) on page 19
- ◆ [“Sybase Requirements”](#) on page 19
- ◆ [“MS SQL Server Requirements”](#) on page 20
- ◆ [“IBM DB2 Requirements”](#) on page 20
- ◆ [“ODBC Requirements”](#) on page 20
- ◆ [“TUXEDO Requirements”](#) on page 20
- ◆ [“UNIFACE Requirements”](#) on page 21
- ◆ [“Citrix MetaFrame Requirements”](#) on page 21
- ◆ [“SAP Requirements”](#) on page 21

- ◆ “ADO Requirements” on page 22
- ◆ “Oracle Forms Server Requirements” on page 22
- ◆ “Java Requirements” on page 22
- ◆ “WWW Requirements” on page 22
- ◆ “Streaming Media Requirements” on page 23

Note: The following middlewares do not have any additional QALoad Windows Player requirements: WAP, Winsock, and NetLoad.

Oracle 7.3.x Requirements

QALoad supports load testing under Oracle when the following requirements are met:

- | | |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| QALoad Script Development Workbench | <ul style="list-style-type: none"> ◆ Oracle 7.3.x or later client installation for recording. ◆ QALoad only supports applications using 32-bit Oracle version of SQL*Net. ◆ Oracle OCI development kit for Windows NT. This is distributed with Oracle’s PRO*C pre-compiler kit or with Oracle’s database for Windows NT. This software must be available on the QALoad Script Development Workbench system to compile the scripts. |
| QALoad Player | <ul style="list-style-type: none"> ◆ Oracle 7.3.x or later client installation for playback. |

Oracle Net8 Requirements

QALoad supports load testing under Oracle Net8 when the following requirements are met:

- | | |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| QALoad Script Development Workbench | <ul style="list-style-type: none"> ◆ Oracle Net8 client installation for recording. ◆ Oracle Call Interface (OCI) development environment for Windows. This is distributed with the Oracle Development Kit as part of the Oracle 8 or Oracle 9 client installation. |
| QALoad Player | <ul style="list-style-type: none"> ◆ Oracle Net8 client installation for playback. |

Sybase Requirements

QALoad supports load testing under Sybase when the following requirements are met:

- | | |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| QALoad Script Development Workbench | <ul style="list-style-type: none"> ◆ Sybase System 10, 11, or 12 client installation for recording. ◆ Sybase’s Open Client library for Windows. If your application uses DBLIB calls, you need to load the DBLIB libraries and header files. If you use Sybase’s newer CTLIB calls, you must load the appropriate CTLIB header files and libraries. |
| QALoad Player | <ul style="list-style-type: none"> ◆ Sybase System 10, 11, or 12 client installation for playback. |

MS SQL Server Requirements

QALoad supports load testing under MS SQL Server when the following requirements are met:

- ◆ QALoad Script Development Workbench
 - ◆ MS SQL Server version 7, or 2000 client installation when using DBLIB.
 - ◆ MS SQL Server C-development environment and SDK for Windows NT or Windows 2000.
- ◆ QALoad Player
 - ◆ SQL Server version 7, or 2000 client installation when using DBLIB.
 - ◆ Supports QALoad Windows Player only.

IBM DB2 Requirements

QALoad supports load testing under IBM DB2 when the following requirements are met:

- ◆ QALoad Script Development Workbench
 - ◆ IBM DB2 6.1 or 7.x client installation.
- ◆ QALoad Player
 - ◆ IBM DB2 6.1 or 7.x client installation.

ODBC Requirements

QALoad supports load testing under ODBC when the following requirements are met:

- ◆ QALoad Script Development Workbench
 - ◆ ODBC 2.0, 2.5, 3.0, or 3.5 client installation.
 - ◆ Visual C++ or ODBC SDK. Libraries from Visual C++, if installed, will be used by default unless ODBC SDK libraries are specified.
- ◆ QALoad Player
 - ◆ ODBC 2.0, 2.5, 3.0, or 3.5 later client installation.
 - ◆ Supports QALoad Windows Player only.

TUXEDO Requirements

QALoad supports load testing under TUXEDO when the following requirements are met:

- ◆ QALoad Script Development Workbench
 - ◆ TUXEDO V6.3, 6.4, or 6.5 client installation.
 - ◆ Complete Windows TUXEDO development environment for recording and compiling.
- ◆ QALoad Player
 - ◆ TUXEDO V6.3, 6.4, or 6.5 client installation.

UNIFACE Requirements

QALoad supports load testing under UNIFACE when the following requirements are met:

- QALoad Script Development Workbench
 - ◆ Development environment of UNIFACE NT 7.2.04 to 7.2.06, complete with the 3GL interface.
 - ◆ Valid UNIFACE NT Software Enable Key (SEK).
- QALoad Player
 - ◆ Development environment of UNIFACE NT 7.2.04 to 7.2.06, complete with the 3GL interface.
 - ◆ Valid UNIFACE NT Software Enable Key (SEK).
 - ◆ Supports QALoad Windows Player only.

Citrix MetaFrame Requirements

QALoad supports load testing under Citrix when the following requirements are met:

- QALoad Script Development Workbench
 - ◆ Citrix ICA client installation version 7.100 or higher.
 - ◆ Citrix MetaFrame 1.8 or MetaFrame XP server.
 - ◆ Microsoft Windows 2000 Service Pack 2 or XP Professional
 - ◆ Microsoft Internet Explorer 6 Service Pack 1.
- QALoad Player
 - ◆ Citrix ICA client installation version 7.100 or higher.
 - ◆ Supports QALoad Windows Player only.
 - ◆ Microsoft Windows 2000 Service Pack 2 or XP Professional
 - ◆ Microsoft Internet Explorer 6 Service Pack 1.
 - ◆ Mid-level Pentium III PC with 256 MB of RAM. Compuware strongly recommends a minimum of 512 MB of RAM.

SAP Requirements

QALoad supports load testing under SAP when the following requirements are met:

- QALoad Script Development Workbench
 - ◆ Appropriate SAP client installation version 4.0B, 4.5, 4.6D, or 6.20. Version 6.20 must be at patch level 40 or later.
 - ◆ Appropriate SAP server patches installed:
 - ◇ SAP 4.6C server: patch level 32 or later
 - ◇ SAP 4.6D server: patch level 21 or later
 - ◇ SAP 6.10 server: patch level 17 or later
 - ◆ Microsoft Windows 2000 Service Pack 2 or XP Professional
- QALoad Player
 - ◆ Appropriate SAP client installation version 4.0B, 4.5, 4.6D, or 6.20 for playback. Version 6.20 must be at patch level 40 or later.
 - ◆ Supports QALoad Windows Player only.

- ◆ Mid-level Pentium III PC with 256 MB of RAM. Compuware strongly recommends a minimum of 512 MB of RAM.
- ◆ Microsoft Windows 2000 Service Pack 2 or XP Professional

ADO Requirements

QALoad supports load testing under ADO when the following requirements are met:

- | | |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| QALoad Script Development Workbench | <ul style="list-style-type: none"> ◆ ADO 2.1, 2.5, or 2.6 for recording. ◆ ADO 2.6 or 2.7 required for script compilations. |
| QALoad Player | <ul style="list-style-type: none"> ◆ ADO 2.6 or 2.7 required for script playback. ◆ Supports QALoad Windows Player only. |

Oracle Forms Server Requirements

QALoad supports load testing under Oracle Forms Server when the following requirements are met:

- | | |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| QALoad Script Development Workbench | <ul style="list-style-type: none"> ◆ Java Development Kit 1.3 required for developing OFS scripts. <p>Note: Java Development Kit 1.4 is not supported for OFS.</p> <ul style="list-style-type: none"> ◆ Support for SSL-enabled recording is valid only for Oracle 9iAS, Release 2. |
| QALoad Player | <ul style="list-style-type: none"> ◆ Java 2 Runtime Environment 1.3 (1.3.0_02 is provided on the QACenter CD) to run OFS scripts. <p>Note: Java Development Kit 1.4 is not supported for OFS.</p> <ul style="list-style-type: none"> ◆ Supports QALoad Windows Player only. |

Java Requirements

QALoad supports load testing of J2EE components when the following requirements are met:

- | | |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| QALoad Script Development Workbench | <ul style="list-style-type: none"> ◆ Java Development Kit 1.3 or 1.4 required for developing Java scripts. |
| QALoad Player | <ul style="list-style-type: none"> ◆ Java 2 Runtime Environment 1.3, or 1.4 (1.3.0_02 is provided on the QACenter CD) to run Java scripts. |

WWW Requirements

QALoad supports load testing under WWW when the following requirements are met:

QALoad Script Development Workbench

- ◆ Netscape Communicator 4.7.x, Netscape 6.x, or Internet Explorer 5.5 or later.

QALoad Player

- ◆ NTLM playback is not supported on UNIX.
- ◆ No additional QALoad Windows Player requirements.

Streaming Media Requirements

QALoad supports Streaming Media under WWW when the following requirements are met:

QALoad Script Development Workbench

- ◆ Netscape Communicator 4.7.x and Netscape 6.x or Internet Explorer 5.5 or later.

QALoad Player

- ◆ RealOne Player Version 2.0 Build 6.0.x, or Windows Media Player 7.x.

Note: Streaming Media playback will not work with Player versions other than stated above.

QALoad UNIX Player Requirements

The QALoad Player and associated utilities are supported on AIX, Linux, HP-UX, and Solaris. The following sections contain the requirements for each operating system:

UNIX Player Requirements for AIX

- ◆ AIX 5L 5.1.
- ◆ 100 MB minimum available disk space.
- ◆ ANSI C Compiler for compiling scripts. Compuware requires IBM C and C++ Compilers, version 3.6.6 (shipped with IBM VisualAge) or VisualAge version 5.0. Compuware also supports GNU GCC Compiler, version 3.0.1.
- ◆ Java Development Kit 1.3 or 1.4 for developing Java scripts. Java Development Kit 1.3 for developing OFS scripts.
- ◆ TCP/IP communications.
- ◆ Appropriate client application environment (see [“UNIX Player Middleware Requirements”](#) on page 24).

UNIX Player Requirements for Linux

- ◆ Red Hat Linux 7.1 and 7.2.
- ◆ 100 MB minimum available disk space.
- ◆ Compuware requires the Linux system provided GNU GCC Compiler.
- ◆ Java Development Kit 1.3 or 1.4 for developing Java scripts. Java Development Kit 1.3 for developing OFS scripts.
- ◆ TCP/IP communications.
- ◆ Appropriate client application environment (see [“UNIX Player Middleware Requirements”](#) on page 24).

UNIX Player Requirements for HP- UX

- ◆ HP-UX 11.0 and HP-UX 11i (11.11).
- ◆ 100 MB minimum available disk space.
- ◆ ANSI C Compiler for compiling scripts. Compuware requires Softbench 6.0, version D or later with the aCC version A.03.27 or later Compiler. Compuware also supports GNU GCC Compiler, version 3.0.1.
- ◆ Java Development Kit 1.3 or 1.4 for developing Java scripts. Java Development Kit 1.3 for developing OFS scripts.
- ◆ TCP/IP communications.
- ◆ Appropriate client application environment (see “UNIX Player Middleware Requirements” on page 24).
- ◆ For HP-UX 11.00, the following patches:
 - ◇ PHCO_22314— libc cumulative patch
 - ◇ PHCO_19666— libpthreads cumulative patch
 - ◇ PHKL_13121— POSIX semaphore deadlock/hang
 - ◇ PHSS_14582— mili.a patch
 - ◇ PHSS_21950— LIBCL patch.

UNIX Player Requirements for Solaris

- ◆ Solaris 2.6, 2.7, or Solaris 8.
- ◆ 100 MB minimum available disk space.
- ◆ ANSI C Compiler for compiling scripts. Compuware requires Sun Workshop Compiler, version 4.2 or 5.0, or Sun Forte 6.0. Compuware also supports GNU GCC Compiler version 3.0.3.
- ◆ Java Development Kit 1.3 or 1.4 for developing Java scripts. Java Development Kit 1.3 for developing OFS scripts.
- ◆ TCP/IP communications.
- ◆ Appropriate client application environment (see “UNIX Player Middleware Requirements” on page 24).

Required: Compuware recommends that you have a user ID set up on the Player system specifically to run the Player software. For example, set up a user ID (qaload) with a home directory of /usr/qaload or /home/qaload.

UNIX Player Middleware Requirements

The UNIX system running the QALoad UNIX Player may need to meet specific requirements based upon which middleware you will be testing. See the following middleware-specific requirements:

UNIX Player Requirements for Oracle 7 and Oracle 8

- ◆ Oracle OCI development kit for UNIX installed on one of the QALoad Player systems to compile the scripts. The OCI development kit is distributed with Oracle Enterprise Server development libraries and client.

UNIX Player
Requirements for
Sybase

- ◆ Sybase’s Open Client library for UNIX. If your application uses DBLIB calls, you need to load Sybase’s DBLIB libraries and header files. If you use Sybase’s newer CTLIB calls, you must load the appropriate CTLIB header files and libraries.

UNIX Player
Requirements for
TUXEDO

- ◆ Complete UNIX TUXEDO V6.3, 6.4, and 6.5 workstation installation including the /include and /lib directories.

UNIX Player
Requirements for DB2

- ◆ Compuware requires that the DB2 6.1 or 7.1 client environment is setup and functional prior to the installation of QALoad.

Required: The following middlewares do not have any additional QALoad UNIX Player requirements: WWW, WAP, Winsock, and Oracle Forms Server.

Installing QALoad

This section explains the installation process for QALoad. Please review “[System Requirements](#)” on page 17 to ensure that QALoad will install and operate properly on your workstation.

Before proceeding with the QALoad installation, Compuware recommends that you review the QALoad Release Notes which includes information about new features, technical notes, and known issues. In addition, it documents recent changes that may not be included in your QALoad documentation. Please review this information carefully; the Release Notes document is updated as new product information becomes available. To review the Release Notes prior to installation, see “[Before Installation](#)” in the “[Getting Started](#)” chapter.

Required: Compuware recommends that you exit all non-essential Windows programs before running this setup program. Some Windows programs may interfere with the installation process.

If a previous version of QALoad is installed on your computer, or if you have any Beta version installed, Compuware recommends that you back up your data and uninstall QALoad before installing the new version. Failure to do so may cause problems.

To perform the installation of QALoad, follow these steps:

- 1 Log on as a user with administrative permissions.
- 2 Insert the QACenter installation CD in the CD-ROM drive. The QACenter CD browser should automatically appear. If it does not, navigate to the root directory and run the setup.exe file.
- 3 Click **Install QACenter Products**.
- 4 Click **Install QALoad**. The Welcome dialog box appears.
- 5 Read the welcome screen and click **Next**. The License Agreement dialog box appears.
- 6 Read the license agreement and click **Yes** to accept the terms of the agreement. The Customer Information dialog box appears.
- 7 Type your name and company in the **User Name** and **Company Name** fields. Click **Next**. The Choose Destination Location dialog box appears.
- 8 Select a location for the QALoad installation.
 - ◇ By default, QALoad installs in the folder x:\Program Files\Compuware\QALoad where x is the drive where Windows resides on your computer.
 - ◇ To specify a different path, click the **Browse** button and select an existing folder or type the path name in the **Path** field. Click **OK**.
- 9 Click **Next**. The Select Components dialog box appears.
- 10 Highlight a component to view a brief description. Select the components you want to install. See [Table 2-1](#) on page 14 for details on each component.
 - ◇ **Script Development Workbench:** Contains all of the elements necessary for recording, converting, compiling, and modifying test scripts. Select the EasyScript component(s) for which you are licensed. Compuware recommends that you do not select components for which you are not licensed because you will not be able to create test scripts with those components.
 - ◇ **Conductor:** Controls the QALoad Players and manages tests. The QALoad Conductor and Analyze must be installed on the same workstation for reporting purposes. QALoad Analyze will be automatically selected for you as well.
 - ◇ **Players:** Emulates users by running test scripts that mimic user transactions. Each QALoad Player type can be selected separately for installation. The QALoad Player for running Java scripts is automatically installed with the Windows and UNIX Players.

- ◇ **Analyze:** Allows you to view timing information from the test in table or graph format.
 - ◇ **Server Analysis Agent:** Monitors server, application, or database use during a load test. QALoad Windows Player will be automatically selected for you as well. The QALoad Server Analysis Agent requires that the QALoad Windows Player be installed on the same workstation.
 - ◇ **Vantage Agent:** This option will not be available if the Vantage Agent is already installed, or if the machine's operating system is Microsoft Windows XP. Allows you to capture trace data on Player machines. Application Vantage uses this captured data to analyze application performance problems. **Note:** The Vantage Agent version must match the version of the Vantage Console Installed.
 - ◇ **NetLoad Server:** The NetLoad UDP and TCP server files are application files that enable NetLoad to perform UDP and TCP testing.
- Make your selection(s) and click **Next**. The Select Program Folder dialog box appears.

11 Specify a location for the QALoad program shortcuts. You may type a new folder name, or select one from the existing folders list. Click **Next**. The Start Copying Files dialog box appears.

12 Review the summary of the settings that you specified and click **Next** to begin copying the program files. The Setup Status dialog box displays the progress of the installation.

13 After the installation completes, the Setup Complete dialog box appears. Depending on the circumstances, you may have the following options:

- ◇ **Display Release Notes:** Choose to review the information in the ReleaseNotes.htm file. This file contains information about new features, technical notes, and known issues that may enhance or impact QALoad's performance. Release Notes contain recent changes that may not be included in your QALoad product documentation.
- ◇ **Register for FrontLine:** Choose to review the information on FrontLine technical support site. FrontLine provides fast access to critical information such as documentation, frequently asked questions, and product fixes. The first time you access FrontLine, you are required to register and obtain a password.

- ◇ **Restart Your Computer:** You may be prompted to restart your computer. If you are prompted to restart your computer, you may choose to restart it now (recommended) or to restart it later.

14 Click **Finish** to complete the installation of QALoad.

15 If you purchased the EasyScript for Secure WWW module to test SSL (Secure Sockets Layer) or HTTPS calls that your browser/server may make, you will receive the appropriate encryption module on CD. To install the module, insert the CD into the CD-ROM drive, then double-click the file `setup.exe` in the `win32` folder on the CD.

Where To Go Next

- ◆ The trial license that is supplied with your QACenter product allows you to install the product and run it for a specific time period without first installing a license. During this trial period, you will be informed of how much evaluation time remains.

At any time during the evaluation period, you can obtain and install a permanent license. When the evaluation period expires, you **must** obtain a license and install it before you can successfully run this product. See the *Distributed License Management Installation Guide* for instructions on installing a license. To access this online book:

- a Insert the QACenter CD into the CD-ROM drive. If the CD browser does not automatically start, navigate to the CD's root directory and run `setup.exe`.
- b Click **View QACenter Documentation**.
- c From the bookshelf, select the *Distributed License Management Installation Guide*.
- ◆ If Adobe Acrobat or Acrobat Reader is not installed on your computer, click **Install 3rd Party Software**, then click **Install Adobe Acrobat Reader** from QACenter's CD browser. Adobe Acrobat or Acrobat Reader is required to view online books in PDF format.
- ◆ To install a QALoad Windows Player on an additional workstation, follow the instructions on the previous pages. However, on the Select Components dialog box, select to install **only** the QALoad Windows Player and deselect all other components.
- ◆ To install a UNIX Player, see [“UNIX Player Installation”](#) on page 29.
- ◆ If you are ready to begin using QALoad, refer to the *QALoad Testing User's Guide*.
- ◆ For information about modifying, repairing, or removing your QALoad installation, see [Chapter 3, “Maintaining the Installation”](#) on page 39.

UNIX Player Installation

This section explains the procedures for installing a Player on a UNIX system. The necessary UNIX Player software is distributed with your QALoad Windows installation. You can choose to install via a tar file or use the vendor-specific package installation mechanism.

Installing Via Tar File

Load the Player Files

To load the appropriate files for QALoad runtime playback onto UNIX, you must FTP the files to the UNIX system and run the installation script. The files are located in the `\UNIX\<platform>` directory of your QALoad installation (for example,

`c:\Program Files\Compuware\QALoad\UNIX\Solaris`).

- 1 FTP, in binary mode, the tar file and installation script file to the desired installation directory, `<installDir>`, on the UNIX system. The installation directory must not contain a previous version of QALoad.
- 2 Log on to the UNIX system.
- 3 On the UNIX system, change directories to `<installDir>`.
- 4 Type `chmod 755 QALoadInstall`
- 5 Run the installation file by typing `./QALoadInstall` and follow the prompts.

Add the QALoad library directory, `<installDir>/lib`, to the library path environment variable on your UNIX system. The name of this variable is specific to the operating system. The following table identifies the name of the library path environment variable for the various UNIX operating systems that are supported by QALoad:

Table 2-2. Library Path Environment Variables

Operating System	Library Path Name
AIX	LIBPATH
HP-UX	SHLIB_PATH
Linux	LD_LIBRARY_PATH
Solaris	LD_LIBRARY_PATH

- 6 If you are replaying Oracle Forms Server (OFS) or EasyScript for Java scripts, make the following changes to the environment on the UNIX system:
 - ◇ **AIX:** Add the path of `libjvm.a` to the **LIBPATH** environment variable.
 - ◇ **HP-UX:** Add the path of `libjvm.sl` to the **SHLIB_PATH** environment variable. Also add the path of `libjvm.sl` to the **LD_PRELOAD** environment variable; this entry must end with `libjvm.sl`.
 - ◇ **Linux:** Add the paths of `libjvm.so` and `libhpi.so` to the **LD_LIBRARY_PATH** environment variable. You must also add the fully-qualified path of `libhpi.so` to the **LD_PRELOAD** environment variable; this entry must end with `libhpi.so`.
 - ◇ **Solaris:** Add the path of `libjvm.so` to the **LD_LIBRARY_PATH** environment variable.
- 7 If you are using database middlewares on any platform, make the following change:
 - ◇ For **Oracle**, add `$(ORACLE_HOME)/lib` to the appropriate library path environment variable.
 - ◇ For **Sybase**, add `$(SYBASE)/lib` to the appropriate library path environment variable.
 - ◇ For **Tuxedo**, add `$(TUXDIR)/lib` to the appropriate library path environment variable.
 - ◇ For **DB2**, add `$(INSTHOME)/sql/lib/lib` to the appropriate library path environment variable.
- 8 If you purchased the EasyScript for Secure WWW module to test SSL (Secure Sockets Layer) or HTTPS calls that your browser/server may make, you will find an encryption module on the second CD. This module must first be installed on a Windows system. For more information about installing this module, see [step 15](#) on [page 28](#).

After installing the module on a Windows system, FTP the two operating system-specific encryption libraries to the `<installDir>` on the UNIX system using binary mode. The encryption libraries can be found in the `\UNIX\<platform>\player` directory of the QALoad installation, such as

```
c:\Program Files\Compuware\QALoad\UNIX\Solaris\player). These two libraries replace the libdo_www and libg++do_www libraries on your UNIX system.
```

- 9 Ensure that the Web Library has executable permission. This can be done by running `chmod +x <libraryName>` on the two library files.
- 10 Start the Player Agent by typing `./loadagent`.

Required: If you restart the UNIX system, you will have to start the Player Agent manually by typing `./loadagent` in the installation directory.

Installing Via Package

Installing a UNIX Player on AIX

Load the Player Files

To load the appropriate package file for QALoad runtime playback onto AIX, you must either mount the installation CD onto the AIX system or FTP the package file(s) from the installation CD to the UNIX system. Once the package is available on the AIX system, use “`smit`” to install the software. The package is located in the `<CD drive>/cpwr/qaload/aix` directory of your QALoad installation CD.

Command Line Installation

To install the UNIX Player on AIX, perform the following steps:

- 1 If using FTP:
 - Use binary mode to copy the package file `QACPE.bff.Z` to the AIX system.
 - Log on as `root`.
- If using the CD:
 - Log on as `root`.
 - Mount the CD onto the AIX system.
- 2 Change directory (`cd`) to where the package file was placed. Note that “`root`” must have write permissions in this directory.
- 3 Uncompress the package file by running the following command:
`uncompress QACPE.bff.Z`
This will expand the compressed package file and create the installable package `QACPE.bff`.
- 4 From the command prompt, type the following command:
`smit`
- 5 From the System Management screen, select **Software Installation and Maintenance** and press **Enter** on the keyboard.
- 6 Select **Install and Update Software** and press **Enter** on the keyboard.
- 7 Select **Install Software** and press **Enter** on the keyboard.

- 8 Type or select the directory where the `QACPE.bff` file can be found and press **Enter** on the keyboard.
- 9 Press **Enter** twice. When the installation is complete, the **COMMAND STATUS** screen appears.
- 10 Locate the **Result** column and verify that the package installation was successful.
- 11 Add `/opt/QALoad/lib` to the **LIBPATH** environment variable.
- 12 If you are replaying Oracle Forms Server (OFS) or EasyScript for Java scripts, add the path of `libjvm.a` to the **LIBPATH** environment variable.
- 13 If you are using database middlewares, change the **LIBPATH** environment variable as indicated below:
 - ◇ For **Oracle**, add `$(ORACLE_HOME)/lib`
 - ◇ For **Sybase**, add `$(SYBASE)/lib`
 - ◇ For **Tuxedo**, add `$(TUXDIR)/lib`
 - ◇ For **DB2**, add `$(INSTHOME)/sql/lib/lib`
- 14 If you purchased the EasyScript for Secure WWW module to test SSL or HTTPS calls, you will find an encryption package on the second CD. To install this package, repeat steps 1 through 10 above. The packages are located in the `<CD drive>/aix` directory and are named either `QACPEEXP.bff.z`, for 40-bit encryption or `QACPE128.bff.z` for 128-bit encryption.

Required: The encryption package must be installed on the same directory as the QACPE package.

- 15 Change directory (`cd`) to `/opt/QALoad`.
- 16 Start the Player Agent by typing `./loadagent`.

Installing a UNIX Player on Linux

Load the Player Files

To load the appropriate files for QALoad runtime playback onto Linux, you must either mount the installation CD onto the Linux system or FTP the package file(s) from the installation CD to the UNIX system. Once the package is available on the Linux system, use “`rpm`” to install the software. The package is located in the `<CD drive>/cpwr/qaload/linux` directory of the QALoad installation CD.

Command Line Installation

To install the UNIX Player on Linux, perform the following steps:

- 1 If using FTP:
 - Use binary mode to copy the package file `QACPE.rpm` to the Linux system.
 - Log on as `root`.
- If using the CD:
 - Log on as `root`.
 - Mount the CD onto the Linux system.
- 2 Change (`cd`) directory to where you copied the package file. Note that "`root`" must have write permissions in this directory.
- 3 To install the QALoad Player to the default directory of `/opt/QALoad`, execute the following command:

```
rpm -Uvh QACPE.rpm
```
- 4 Add `/opt/QALoad/lib` to your `LD_LIBRARY_PATH` environment variable.
- 5 If you are replaying Oracle Forms Server (OFS) or EasyScript for Java scripts, add the paths of `libjvm.so` and `libhpi.so` to the `LD_LIBRARY_PATH` environment variable. You must also add the fully-qualified path of `libhpi.so` to the `LD_PRELOAD` environment variable; this entry must end with `libhpi.so`.
- 6 If you are using these database middlewares, change the `LD_LIBRARY_PATH` environment variable as indicated:
 - ◇ For **Oracle**, add `$(ORACLE_HOME)/lib`
 - ◇ For **Sybase**, add `$(SYBASE)/lib`
 - ◇ For **Tuxedo**, add `$(TUXDIR)/lib`
 - ◇ For **DB2**, add `$(INSTHOME)/sql/lib/lib`
- 7 If you purchased the EasyScript for Secure WWW module to test SSL or HTTPS calls, you will find an encryption package on the second CD. To install this package, repeat steps 1 through 3 above. The package is located in the `<CD drive>linux` directory and is named either `QACPEEXP.rpm` for 40-bit encryption or `QACPE128.rpm` for 128-bit encryption.

Required: The encryption package must be installed on the same directory as the QACPE package.

- 8 Change directory (`cd`) to the directory where QALoad was installed.
- 9 Start the Player Agent by typing `./loadagent`.

Installing a UNIX Player on HP-UX

Load the Player Files

To load the appropriate package file for QALoad runtime playback onto HP-UX, you must either mount the installation CD onto the HP-UX system or FTP the package file(s) from the installation CD to the UNIX system. Once the package is available on the HP-UX system, you can use "swpackage" to install the software. The package is located in the `<CDdrive>/cpwr/qaload/hpux` directory of your QALoad installation CD.

Note: If you wish to install the vendor-specific package using the graphical installation, refer to the *HP-UX System Administration Handbook and Toolkit*.

Command Line Installation

To install the UNIX Player on HP-UX, perform the following steps:

1 If using FTP:

- Use binary mode to copy the package file `QACPE.depot.Z` to the HP-UX system.
- Log on as `root`.

If using the CD:

- Log on as `root`.
- Mount the CD onto the HP-UX system.
- Copy the `QACPE.depot.Z` package file onto the system. **Note:** The default depot on HP-UX is `/var/spool/sw`.

2 Change (`cd`) directory to where you copied the package file. Note that "root" must have write permissions in this directory.

3 Uncompress the package file by running the following command:

```
uncompress QACPE.depot.Z
```

This will expand the compressed package file and create the installable package `QACPE.depot`.

4 Execute the following command:

```
swinstall -s <machineName>:<depotName> QACPE
```

This will install the QACenter Performance Edition Installation and Configuration Guide package on the `/opt/QALoad` directory. If you wish to relocate the installation to a different directory, type the following command:

```
swinstall -s <machineName>:<depotName> QACPE,1=  
<installDir>
```

For either of these commands, `<depotName>` must be the full path name of the QALoad depot package.

5 Add `/<installDir>/lib` to the `SHLIB_PATH` environment variable.

- 6 If you are replaying Oracle Forms Server (OFS) or EasyScript for Java scripts, add the path of `libjvm.sl` to the **SHLIB_PATH** variable. You must also add the path of `libjvm.sl` to the **LD_PRELOAD** environment variable; this entry must end with `libjvm.sl`.
- 7 If you are using database middlewares, change the **LIBPATH** environment variable as indicated below:
 - ◇ For **Oracle**, add `$(ORACLE_HOME)/lib`
 - ◇ For **Sybase**, add `$(SYBASE)/lib`
 - ◇ For **Tuxedo**, add `$(TUXDIR)/lib`
 - ◇ For **DB2**, add `$(INSTHOME)/sql1lib/lib`
- 8 If you purchased the EasyScript for Secure WWW module to test SSL or HTTPS calls, you will find an encryption package on the second CD. To install this package, repeat steps 1 through 4 above. The package is located in the `<CD drive>/hpux` directory and is named either `QACPEEXP.depot.Zfor40-bitencryption` or `QACPE128.depot.Zfor128-bit encryption`.

Required: The encryption package must be installed on the same directory as the QACPE package.

- 9 Change directory (`cd`) to the installation directory, which is either `/opt/QALoad` or `<installDir>`.
- 10 Start the Player Agent by typing `./loadagent`.

Installing a UNIX Player on SOLARIS

Load the Player Files

To load the appropriate package file for QALoad runtime playback onto Solaris, you must either mount the installation CD onto the Solaris system or FTP the package file(s) from the installation CD to the UNIX system. Once available on the Solaris system, you can use “`pkgadd`” to install the software. The package is located in the `<CD drive>/cpwr/qaload/solaris` directory of your QALoad installation CD.

Note: If you wish to install the vendor-specific package using the graphical installation, refer to the *Solaris System Administrator’s Guide 3rd Edition*.

Command Line Installation

To install the UNIX Player on Solaris, perform the following steps:

- 1 If using FTP:
 - Use binary mode to copy the package file `QACPE.tar.Z` to the Solaris system.
 - Log on as `root`.

If using the CD:

- Log on as `root`.
 - Mount the CD onto the Solaris system.
 - Copy the `QACPE.tar.Z` package file onto the system.
- 2 Change (`cd`) to the directory where you copied the package file. Note that "`root`" must have write permissions in this directory.
 - 3 Uncompress the package file by running the following command:

```
uncompress QACPE.tar.Z
```

This will expand the compressed package file and create the package tar file `QACPE.tar`.
 - 4 Extract the contents of the tar file by running the following command:

```
tar -xvf QACPE.tar
```

This will create the directory structure required for installation.
 - 5 Execute the following command:

```
pkgadd -d .
```

This will display the package to install and prompt you to select the package.
 - 6 Select the QACenter Performance Edition package and press **Enter** on your keyboard. You will be prompted to **Enter path to package base directory**. This is the path where the package will be installed. For example, typing `/opt` will install the package to `/opt/QALoad`.
 - 7 Type the base directory to begin installation.
 - 8 When the installation is complete, the package to install selection displays again. Select **q** to quit.
 - 9 Add `/<base directory>/QALoad/` to your `LD_LIBRARY_PATH` environment variable.
 - 10 If you are replaying Oracle Forms Server (OFS) or EasyScript for Java scripts, add the path of `libjvm.so` to the `LD_LIBRARY_PATH` environment variable.
 - 11 If you are using database middlewares, change the `LD_LIBRARY_PATH` environment variable as indicated:
 - ◇ For **Oracle**, add `$(ORACLE_HOME)/lib`
 - ◇ For **Sybase**, add `$(SYBASE)/lib`
 - ◇ For **Tuxedo**, add `$(TUXDIR)/lib`
 - ◇ For **DB2**, add `$(INSTHOME)/sql/lib/lib`

- 12 If you purchased the EasyScript for Secure WWW module to test SSL or HTTPS calls, you will find an encryption package on the second CD. To install this package, repeat steps 1 through 8 above. The package is located in the `<CD drive>/solaris` directory and is named either `QACPEEXP.tar.Z` for 40-bit encryption or `QACPE128.tar.Z` for 128-bit encryption.

Required: The encryption package must be installed on the same directory as the QACPE package.

- 13 Change directory (`cd`) to the installation directory, which is either `/opt/QALoad` or `<base directory>`.


- 14 Start the Player Agent by typing `./loadagent`

Where to Go Next

To begin using QALoad, refer to the *QALoad Testing User's Guide*.

Chapter 3

Maintaining the Installation



- ◆ Accessing Maintenance Mode
- ◆ Modifying an Installation
- ◆ Repairing an Installation
- ◆ Removing a Product

Accessing Maintenance Mode

There are two methods for accessing a QACenter product's maintenance mode: from the QACenter CD or from the Windows Control Panel.

Required: Compuware recommends that you exit all non-essential Windows programs before running this setup program. Some Windows programs may interfere with the installation process.

Accessing Maintenance Mode from the Windows Control Panel

- 1 Click the Windows **Start** button and choose **Settings>Control Panel**. The Control Panel window appears.
- 2 **Windows 9x/NT:** Choose the **Add/Remove Programs** icon. The Add/Remove Programs Properties dialog box appears. Select the QACenter product to maintain and click **Add/Remove**.

Windows 2000: Choose the **Add/Remove Programs** icon. The Add/Remove Programs dialog box appears. Select the QACenter product to maintain and click **Change/Remove**.

You are presented with the three maintenance mode options: modify, repair, and remove. For more information about these options, see the appropriate section in this chapter.

Accessing Maintenance Mode from the QACenter CD

- 1 In the CD-ROM drive, insert the QACenter CD containing the same version of the product that you have installed. The QACenter CD browser should automatically appear. If it does not, navigate to the root directory and run the `setup.exe` file.
- 2 Click **Install QACenter Products**.
- 3 Click **Install** *product name* (where *product name* is the name of the product that you want to maintain).

You are presented with three maintenance mode options: modify, repair, and remove.

Modifying an Installation

For products with optional components, you may want to add or remove a component.

Rather than uninstall and re-install the product, you can modify your installation.

Modifying Products With Optional Components

- 1 Access maintenance mode using one of the two methods described at the beginning of this chapter.
- 2 Select the **Modify** option. Click **Next**. The Select Components dialog box appears allowing you to add or remove components.
- 3 Click **Next**. Setup will add or remove the appropriate components.
- 4 After modifying, you may be prompted to restart your computer. If you are prompted to restart your computer, you may choose to restart it now (recommended) or to restart it later.
- 5 Click **Finish** to complete the maintenance.

Repairing an Installation

There may be times when you will need to repair a damaged QACenter product installation. This could be due to an inadvertent deletion or

corruption of the program. To repair your QACenter product, follow these steps:


- 1 Access maintenance mode using one of the two methods described in “Accessing Maintenance Mode” at the beginning of this chapter.
- 2 Select the **Repair** option. Click **Next**. Setup will repair the specified QACenter product.
- 3 After repairing, you may be prompted to restart your computer. If you are prompted to restart your computer, you may choose to restart it now (recommended) or to restart it later.
- 4 Click **Finish** to complete the maintenance.

Removing a Product

If you want to remove a QACenter product from a PC, follow these steps:

- 1 Access maintenance mode using one of two methods described at the beginning of this chapter.
- 2 Select the **Remove** option. Click **Next**. The Confirm File Deletion dialog box appears.
- 3 Click **OK**. Setup will remove the specified QACenter product from your PC. If your product uses a database repository, it will not be deleted.
- 4 After uninstalling, you may be prompted to restart your computer. If you are prompted to restart your computer, you may choose to restart it now (recommended) or to restart it later.
- 5 Click **Finish** to complete the maintenance.

Index



A

- access methods
 - maintenance [39](#)
- ADO
 - requirements [22](#)
- AIX
 - UNIX Player requirements [23](#)
- Analyze
 - system requirements [18](#)
- Application Expert [15](#)
- Application Vantage
 - Remote Agent [15](#)

B

- before installing [10](#)
 - new version [25](#)
 - QALoad [13](#)
- beta version
 - uninstalling (QALoad) [25](#)
- bulk checkout
 - QALoad Conductor [16](#)

C

- Citrix
 - requirements [21](#)

- component
 - requirements [17](#)
- components
 - QALoad [13](#)
- Compuware technical support
 - FrontLine Web site [6](#)
- Compuware World Wide Web sites [6](#)
- concurrent Conductor licensing [16](#)
- Conductor
 - system requirements [18](#)
- customer support [7](#)

D

- descriptions
 - QACenter products [9](#)

F

- FrontLine technical support
 - Web site [6](#)

G

- getting started [9](#)

H

help 7

FrontLine Web site 6

HPUX

UNIX Player requirements 24

I

IBM DB2

requirements 20

installation

planning 13

installation pre-requisites 10

installation types 10

installing

modify product components 40

package (UNIX) 31

process (QALoad) 25

QACenter products prerequisites 9

QALoad 25, 29

repairing a product installation 40

tar file (UNIX) 29

types of installations 10

UNIX Player 29

introduction 5

J

Java

requirements 22

L

licensing

QALoad 16

Linux

UNIX Player requirements 23

load testing

requirements 13

M

Maintaining the Installation 39

maintenance

access methods 39

modify 40

remove 41

repair 40

middleware

UNIX Player requirements 24

modify

maintenance 40

MS SQL Server

requirements 20

N

new version

before installing 25

O

ODBC

requirements 20

operating requirements

QALoad 17

Oracle

requirements 19

Oracle Forms Server

requirements 22

P

package (UNIX)

installing 31

- planning
 - installation 13
 - QALoad installation 13
- planning your installation
 - QALoad 13
- pre-installation 10
- prerequisites for QACenter product installation 9
- process
 - installing QALoad 25

Q

- QACenter
 - FrontLine Web site 6
 - help 6
 - technical support 6
- QACenter products
 - descriptions 9
- QALoad
 - Analyze, requirements 18
 - before installing 13
 - components 13
 - concurrent Conductor licensing 16
 - Conductor, requirements 18
 - installing 25, 29
 - operating requirements 17
 - planning your installation 13
 - Script Development Workbench, requirements 18
 - Server Analysis Agent, requirements 18
 - system requirements 17
 - upgrading 25
 - Windows Player, requirements 18
- QALoad Analyze
 - system requirements 18
- QALoad Conductor
 - bulk checkout 16
 - licensing 16
 - system requirements 18

R

- RealOne Player 23
- Remote Agent
 - Application Vantage 15
- remove
 - maintenance 41
- repair
 - maintenance 40
- requirements
 - ADO 22
 - by component 17
 - Citrix 21
 - IBM DB2 20
 - Java 22
 - load testing 13
 - MS SQL Server 20
 - ODBC 20
 - Oracle 19
 - Oracle Forms Server 22
 - SAP 21
 - Sybase 19
 - Tuxedo 20
 - UNIFACE 21
 - UNIX Player 23
 - WWW 22

S

- SAP
 - requirements 21
- Solaris
 - UNIX Player requirements 24
- Streaming Media 23
 - RealOne Player 23
 - Windows Media Player 23
- support
 - FrontLine Web site 6
- Sybase
 - requirements 19
- system requirements

- AIX on UNIX [23](#)
- complete Windows [17](#)
- HPUX on UNIX [24](#)
- Linux on UNIX [23](#)
- QALoad [17](#)
- QALoad Analyze [18](#)
- QALoad Conductor [18](#)
- Script Development Workbench [18](#)
- Solaris on UNIX [24](#)

T

- tar file (UNIX)
 - installing [29](#)
- technical support [7](#)
 - FrontLine Web site [6](#)
- Tuxedo
 - requirements [20](#)
- types of installation [10](#)

U

- UNIFACE
 - requirements [21](#)
- uninstalling
 - beta version (QALoad) [25](#)
- UNIX Player
 - installing [29](#)
 - middleware requirements [24](#)
 - requirements [23](#)
- UNIX Player requirements
 - AIX [23](#)
 - HPUX [24](#)
 - Linux [23](#)
 - Solaris [24](#)
- upgrading
 - QALoad [25](#)

V

- Vantage Agent [15](#)

W

- Windows
 - system requirements [17](#)
- Windows Media Player [23](#)
- World Wide Web, Compuware sites [6](#)
- WWW
 - requirements [22](#)